

UNF 高壓 45 度彎頭 (一般殼) (JIC 37° Flare Female-Hose Barb)



鐵記號：OA6NJ

編號	螺紋	軟管	外殼 (一般殼) (mm)		螺帽 (mm)
			外徑	內徑	
22	7/16-20	1/4	19.0	14.5	14
42	9/16-18	3/8 之 1/4	19.0	14.5	19
33	1/2-20	5/16	21.0	17.0	17
43	9/16-18	3/8 之 5/16	21.0	17.0	19
44	9/16-18	3/8	24.0	19.0	19
54	3/4-16	1/2 之 3/8	24.0	19.0	23
55	3/4-16	1/2	27.0	22.0	23
65	7/8-14	5/8 之 1/2	27.0	22.0	26
66	7/8-14	5/8	31.0	25.0	26
76	1 1/16-12	3/4 之 5/8	31.0	25.0	32
77	1 1/16-12	3/4	36.0	29.0	32
87	1 5/16-12	1 之 3/4	36.0	29.0	38
88	1 5/16-12	1	45.0	38.0	38
99	1 5/8-12	1 1/4	55.5	47.0	50
AA	1 7/8-12	1 1/2	63.5	54.0	57
DD	2 1/2-12	2	76.0	66.0	72

UNF 高壓 45 度彎頭 (大殼) (JIC 37° Flare Female-Hose Barb)



鐵記號：OA6NJ

編號	螺紋	軟管	外殼 (大殼) (mm)		螺帽 (mm)
			外徑	內徑	
22-1	7/16-20	1/4	20.0	16.0	14
42-1	9/16-18	3/8 之 1/4	20.0	16.0	19
44-1	9/16-18	3/8	24.0	19.5	19
54-1	3/4-16	1/2 之 3/8	24.0	19.5	23
55-1	3/4-16	1/2	28.0	23.0	23
65-1	7/8-14	5/8 之 1/2	28.0	23.0	26
66-1	7/8-14	5/8	31.0	27.0	26
76-1	1 1/16-12	3/4 之 5/8	31.0	27.0	32
77-1	1 1/16-12	3/4	37.0	31.0	32
77-2	1 1/16-12	3/4	36.0	30.0	32
87-1	1 5/16-12	1 之 3/4	37.0	31.0	38
88-1	1 5/16-12	1	45.0	38.5	38
99-1	1 5/8-12	1 1/4	60.0	48.0	50
AA-1	1 7/8-12	1 1/2	73.0	58.0	57
DD-1	2 1/2-12	2	83.0	68.0	72