


Straight Connector JIC 37° Flare-JIC 37° Flare Male



Brass Mark : CPU
Soft Steel Mark : GPU
Stainless Steel Mark : CCU

Item No	Description	Thread		Dimension (mm)				
		T (UNF)	T1 (UNF)	L	L1	L2	L3	H
I22	1/4 X 1/4	7/16- 20	7/16- 20	35				14
I33	5/16 X 5/16	1/2-20	1/2-20	35				14
I42	3/8 X 1/4	9/16-18	7/16-20	36				14
I44	3/8 X 3/8	9/16-18	9/16-18	37				14
I52	1/2 X 1/4	3/4-16	7/16-20	39.5				21
I54	1/2 X 3/8	3/4-16	9/16-18	40.5				21
I55	1/2 X 1/2	3/4-16	3/4-16	42.5				21
I64	5/8 X 3/8	7/8-14	9/16-18	42.5				23
I65	5/8 X 1/2	7/8-14	3/4-16	44.5				23
I66	5/8 X 5/8	7/8-14	7/8-14	46.5				23
I74	3/4 X 3/8	1 1/16-12	9/16-18	46				27
I75	3/4 X 1/2	1 1/16-12	3/4-16	48				27
I76	3/4 X 5/8	1 1/16-12	7/8-14	50				27
I77	3/4 X 3/4	1 1/16-12	1 1/16-12	53				27
I86	1 X 5/8	1 5/16-12	7/8-14	53				33
I87	1 X 3/4	1 5/16-12	1 1/16-12	55				33
I88	1 X 1	1 5/16-12	1 5/16-12	57				33
I98	1 1/4 X 1	1 5/8-12	1 5/16-12	60				41
I99	1 1/4 X 1 1/4	1 5/8-12	1 5/8-12	62				41
IA8	1 1/2 X 1	1 7/8-12	1 5/16-12	65				50
IA9	1 1/2 X 1 1/4	1 7/8-12	1 5/8-12	67				50
IAA	1 1/2 X 1 1/2	1 7/8-12	1 7/8-12	70				50
ID9	2 X 1 1/4	2 1/2-12	1 5/8-12	76				65
IDA	2 X 1 1/2	2 1/2-12	1 7/8-12	79				65
IDD	2 X 2	2 1/2-12	2 1/2-12	85				65