

Straight Female High Pressure Connector PF Female(JIS 30° Concave)-Hose Barb



Soft Steel Mark : OA1NV

Item No	Thread	Hose bore	Outer shell (mm)		Nut (mm)
			OD	ID	
22	1/4-19	1/4	19.0	14.5	17
44	3/8-19	3/8	24.0	19.0	21
55	1/2-14	1/2	27.0	22.0	26
66	5/8-14	5/8	31.0	25.0	29
77	3/4-14	3/4	36.0	29.0	32
88	1-11	1	45.0	38.0	38
99	1 1/4-11	1 1/4	55.5	47.0	50
AA	1 1/2-11	1 1/2	63.5	54.0	57
DD	2-11	2	76.0	66.0	72
Item No	Thread	Hose bore	Outer shell -Big shell (mm)		Nut (mm)
			OD	ID	
22-1	1/4-19	1/4	20.0	16.0	17
44-1	3/8-19	3/8	24.0	19.5	21
55-1	1/2-14	1/2	28.0	23.0	26
66-1	5/8-14	5/8	31.0	27.0	29
77-1	3/4-14	3/4	37.0	31.0	32
88-1	1-11	1	45.0	38.5	38
99-1	1 1/4-11	1 1/4	60.0	48.0	50
AA-1	1 1/2-11	1 1/2	73.0	58.0	57
DD-1	2-11	2	83.0	68.0	72