









SA TYPE (ONE-HAND QUICK COUPLING)

Model		10	15	20	25	30	40
Size		1/8"	3/16"	1/4"	5/16"	3/8"	1/2"
Material		Steel SC / Brass BSBM / Stainless Steel SUS 304					
Connection method	Socket	Female screw [F] / Male screw [M] / Hose nipple [H] / Lock Tube [P]					
	Plug						
Working pressure / Max. working pressure	Steel	15 / 20 (kgf/cm ²)	1.5 / 2.0 (MPa)	213 / 284 (psi)	15 / 20 (bar)		
	Brass	10 / 15 (kgf/cm ²)	1.0 / 1.5 (MPa)	142 / 213 (psi)	10 / 15 (bar)		
	Stainless Steel	15 / 20 (kgf/cm ²)	1.5 / 2.0 (MPa)	213 / 284 (psi)	15 / 20 (bar)		
Seal material: Working temperature range	Standard	NBR: -20°C ~ +80°C (-4°F ~ +176°F)					
	Optional	VITON: -20°C ~ +180°C (-4°F ~ +356°F) EPDM: -40°C ~ +150°C (-40°F ~ +302°F)					
Applicable fluid		Oil / Air / Water					
Use		Pneumatic tool, Pneumatic piping, Pneumatic machinery, Water piping, etc.					



Computer No	Product Sign	Dimension (mm)					
		Ls	D	Cs	A	T	Bs
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	15SH	56.4	18.9	Ø19.5*6HEX*17D	22.5	5.5	3
	20SH	58.4	18.9	Ø19.5*6HEX*17D	25	7.2	4
	25SH	58.4	18.9	Ø19.5*6HEX*17D	25	9	6.2
	30SH	58.9	18.9	Ø19.5*6HEX*17D	25.5	11.3	7
	40SH	65.4	18.9	Ø21.7*6HEX*19D	32	15	9

Computer No	Product Sign	Dimension (mm)					
		Ls	D	Cs	A	T	Bs
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	10SF	42.7	18.9	Ø18.2*6HEX*16D	9	PT1/8"28P	8
	20SF	43.4	18.9	Ø19.5*6HEX*17D	9	PT1/4"19P	9
	30SF	45.4	18.9	Ø21.7*6HEX*19D	11.7	PT3/8"19P	9


Computer No	Product Sign	Dimension (mm)					
		Ls	D	Cs	A	T	Bs
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	10SM	43.4	18.9	Ø19.5*6HEX*17D	9.2	PT1/8"28P	6.2
	20SM	44.4	18.9	Ø19.5*6HEX*17D	11	PT1/4"19P	7
	30SM	44.4	18.9	Ø19.5*6HEX*17D	11	PT3/8"19P	9
	40SM	46.4	18.9	Ø24*6HEX*21D	13	PT1/2"14P	14


Computer No	Product Sign	Dimension (mm)					
		Ls	D	Cs	A	T	Bs
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	10SMS	43.4	18.9	Ø19.5*6HEX*17D	10	PS1/8"28P	5
	20SMS	43.4	18.9	Ø19.5*6HEX*17D	10	PS1/4"19P	8.1
	30SMS	43.4	18.9	Ø19.5*6HEX*17D	10	PS3/8"19P	11.5
	40SMS	46.4	18.9	Ø24*6HEX*21D	13	PS1/2"14P	12.4

Computer No	Product Sign	Dimension (mm)					
		Ls	D	Cs	A	T	Bs
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	20SP	45.7	18.9	Ø19.5*6HEX*17D	11.5	4*6	6.6
	25SP	47.2	18.9	Ø19.5*6HEX*17D	13	5*8	8.2
	30SP	49.7	18.9	Ø19.5*6HEX*17D	15.5	6.5*10	10.2


Computer No	Product Sign	Dimension (mm)					
		Ls	D	Cs	A	T	Bs
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	20SG	46.7	18.9	Ø19.5*6HEX*17D	13.3	7/16"20P	5
	30SG	48.4	18.9	Ø19.5*6HEX*17D	15	9/16"18P	8
	40SG	49.9	18.9	Ø21.7*6HEX*19D	16.5	3/4"16P	10

SA TYPE (ONE-HAND QUICK COUPLING)


 Single Shut-off




Computer No	Product Sign	Dimension (mm)					
		Ls	D	Cs	A	T	Bs
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	10SAP	53.9	18.9	Ø19.5*6HEX*17D	20.5	13	7




Computer No	Product Sign	Dimension (mm)					
		Lp	C	Cp	A	T	Bp
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	15PH	44	15	14	23	5.5	6.2
	20PH	46	15	14	25	7.2	6.2
	25PH	46	15	14	25	9	6.2
	30PH	46	15	14	25	11.3	6.2
	40PH	53	15	20	32	15	6.2




Computer No	Product Sign	Dimension (mm)					
		Lp	C	Cp	A	T	Bp
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	10PF	28	15	Ø16*6HEX*14D	10.5	PT1/8"28P	6.2
	20PF	28	15	Ø19.5*6HEX*17D	12	PT1/4"19P	6.2
	30PF	33	15	Ø24*6HEX*21D	16.1	PT3/8"19P	6.2




Computer No	Product Sign	Dimension (mm)					
		Lp	C	Cp	A	T	Bp
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	10PM	30.9	15	Ø13.7*6HEX*12D	10	PT1/8"28P	6.2
	20PM	34	15	Ø19.5*6HEX*17D	13	PT1/4"19P	6.2
	30PM	34	15	Ø19.5*6HEX*17D	13	PT3/8"19P	6.2
	40PM	34	15	Ø24*6HEX*21D	13	PT1/2"14P	6.2



Computer No	Product Sign	Dimension (mm)					
		Lp	C	Cp	A	T	Bp
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	10PMS	31	15	Ø13.7*6HEX*12D	10	PS1/8"28P	6.2
	20PMS	31	15	Ø19.5*6HEX*17D	10	PS1/4"19P	6.2
	30PMS	31	15	Ø19.5*6HEX*17D	10	PS3/8"19P	6.2
	40PMS	34	15	Ø24*6HEX*21D	13	PS1/2"14P	6.2



Computer No	Product Sign	Dimension (mm)					
		Lp	C	Cp	A	T	Bp
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	20PP	32.5	15	Ø16*6HEX*14D	11.5	4*6	6.2
	25PP	34	15	Ø16*6HEX*14D	13	5*8	6.2
	30PP	36	15	Ø19.5*6HEX*17D	15	6.5*10	6.2



Computer No	Product Sign	Dimension (mm)					
		Lp	C	Cp	A	T	Bp
SUS A2335SAJA BRASS A0135SAJA STEEL A1135SAJA	20PG	34.3	15	Ø19.5*6HEX*17D	13.3	7/16"20P	6.2
	30PG	36	15	Ø19.5*6HEX*17D	15	9/16"18P	6.2
	40PG	37.5	15	Ø21.7*6HEX*19D	16.5	3/4"16P	6.2

Dimension of T: NPT, BSP, etc. are available to produce besides PT. (Welcome to order special threads)