



JOIN BRASS ENTERPRISE CO., LTD.


ZA TYPE (OXYGEN & ACETYLENE QUICK COUPLING)

FOR CUTTER USE


Major Applicable Fluid~ Brass=Iron: Oxygen / Acetylene / Air

Double Shut-off &


Single Shut-off




Computer No	Product Sign	Dimension (mm)					
		Lp	C	Zp	A	T	Bp
AOOZJAZO	P-2	44.6	20.8	Ø21.8*6HEX*19D	10.6	M16*1.5PL	4.6




Computer No	Product Sign	Dimension (mm)					
		Lp	C	Zp	A	T	Bp
AOOZJAZO	P-B	44.6	20.8	Ø21.8*6HEX*19D	10.6	M16*1.5PL	4.6




Computer No	Product Sign	Dimension (mm)					
		Ls	D	Hs	A	T	Bs
AOOZJAAS	20T	48	22	Ø19.5*6HEX*17D	10	M16*1.5PL	6




Computer No	Product Sign	Dimension (mm)					
		Ls	D	A	T	Hs	Bs
AOOZJAAS	206	67.6	22	24	6.5	13	3
AOOZJAAS	208	69.6	22	26	9	13	5




Computer No	Product Sign	Dimension (mm)					
		Lp	C	Zp	A	T	Bp
AOOZJAZO	P-1	44.6	20.4	Ø21.8*6HEX*19D	10.6	M16*1.5P	3.6



Computer No	Product Sign	Dimension (mm)					
		Lp	C	Zp	A	T	Bp
AOOZJAZO	P-A	44.6	20.4	Ø21.8*6HEX*19D	10.6	M16*1.5P	3.6



Computer No	Product Sign	Dimension (mm)					
		Ls	D	Hs	A	T	Bs
AOOZJAAS	10T	46	20	Ø19.5*6HEX*17D	10	M16*1.5P	6



Computer No	Product Sign	Dimension (mm)					
		Ls	D	A	T	Hs	Bs
AOOZJAAS	106	65.6	20	24	6.5	11	3
AOOZJAAS	108	67.6	20	26	9	11	5

Max. pressure: 10 kgf/cm² [1.0 MPa] [142 psi] [10 bar]

Operating temp. range: -20°C ~ +80°C (-4°F ~ +176°F)

Uses: Active / Inertia / Chemical Gas / Vehicle / Mark For Piping